

CW Type Brass Cable Glands

Brass Cable Glands CW Type CW Brass Cable Glands Kits Packs



Standard	EN 50262 : 1999
Sizes of Brass CW Cable glands CW cable gland kits Cable gland packs	20 mm 25mm 32mm 40mm 50mm 63mm 75mm
Application	For indoor or outdoor use with all types of SWA Cable
Optional Threads	METRIC, NPT, BSP, PG or as specified
Material	Brass BS 2874 CZ121 Pb3
Operating Temp.	Standard seals -200 to +800 C
Function	Provide for Environmental Seal in the Cable Outer Sheath,. Also provide mechanical cable retention & electrical continuity.
Finish	Brass Finish, Nickel Finish, Chrome Finish or as specified
Accessories for CW armoured cable glands	Matching Accessories available like PVC Shrouds, Lock Nuts, Earth Tags, REDucers, Adaptors, etc. as per the requirement , Cable glands kits can be offered with PVC shrouds Brass lock nuts and Brass earth tags. LSF Gland kits can also be offered. (Low Smoke and fume)

Technical Data:

Size	Thread Size 'C'		Minimum Length of Thread 'D'	Cable Range	
	MM	INCH		MAX 'A'	MAX 'B'
CW 20S	20	3/4	10	11.80	17.80
CW 40S	40	1.1/2	13	30.40	38.50
CW 20L	20	3/4	10	14.00	20.80
CW 25L	25	1	10	20.30	27.40
CW 25S	25	1	10	18.00	24.00
CW 32L	32	1.1/4	10	26.50	34.20
CW 32S	32	1.1/4	10	24.50	31.00
CW 50S	50	2	13	40.00	47.00
CW 50L	50	2	13	44.00	53.50
CW 40L	40	1.1/2	13	33.20	41.00
CW 63S	63	2.1/2	14	50.00	59.00
CW 63L	63	2.1/2	13.50	56.00	66.00
CW 75S	75	3	15	63.50	73.00
CW 75L	75	3	15	69.00	79.00

Also available in Kit Packaging and also as per the specification.

ADDEESS:

A1metallics INDIA Plot- 1255, GIDC Industrial Estate, Shanker tekri Jamnagar 361004 Gujarat INDIA

CONTACTS:

PHONE : 91-22-43449300/99

FAX : 91-22-22834046

EMAIL : sales@a1metallics.com

[CONTACT US](#) | [BACK TO HOME PAGE](#)

KEYWORDS: