

Cable Glands Brass BW 2 Parts



Brass BW cable Glands



Brass 2 parts BW cable Glands



Brass BW cable Glands



Brass 2 parts BW cable Glands



Brass Cable Glands BW 2 Parts

Function	Provide mechanical Cable Retention & Electrical Wire continuity via Armoured Wire.
Operating Temp.	-800 C to +3000 C
Size of Brass BW Cable Glands	20 mm t25mm 32mm 40mm 50mm 63mm 75mm 90mm
Material	Brass BS 2874 CZ121 Pb3
Accessories	Matching Accessories available like PVC Shrouds, Lock Nuts, Earth Tag, Reducers, Adaptors, etc. as per the requirement . LSF Cable glands can also be offered. (Low smoke and fume) in kit form with earth tags PVC shrouds and lock nuts of steel or Brass.
Optional Threads	METRIC, NPT, BSP, PG or as specified
Standard	BS 6121
Application	Dry Indoor, for use with all types of SWA Cable
Finish	Brass Finish, Nickel Finish, Chrome Finish or as specified

Technical Data:

Size	Thread Size 'C'		Minimum Length of Thread 'D'	Cable Range	
	MM	INCH		MAX 'A'	MAX 'B'
BW 20L	20	3/4	10	14.00	18.50
BW 20S	20	3/4	10	13.00	15.50
BW 32L	32	1.1/4	10	27.00	33.90
BW 25L	25	1	10	20.50	26.00
BW 40L	40	1.1/2	15	33.00	41.50
BW 50L	50	2	15	44.00	52.00
BW 75S	75	3	15	63.00	74.00
BW 63S	63	2.1/2	15	51.00	59.20
BW 50S	50	2	15	38.50	47.00
BW 63L	63	2.1/2	15	56.50	65.50
BW 75L	75	3	15	68.50	79.50
BW 90L	90	3.1/2	20	80.50	91.00

ADDEESS:

A1metallics INDIA Plot No.10 GIDC Industrial Estate, Shanker Tekri Jamnagar Gujarat, India.

CONTACTS:

PHONE : 91-22-43449300/27

FAX : 91-22-22834046

EMAIL : sales@a1metallics.com

[CONTACT US](#) | [BACK TO HOME PAGE](#)

KEYWORDS: