

**Metric Cable Glands Brass Strain Relief**

**Brass Cable Glands Metric Strain Relief glands Nickel Plated Brass Cable glands**



**Metric Cable Glands Brass Strain Relief**

New Page 1

**Brass Cable Glands Metric Strain Relief glands Nickel Plated Brass Cable glands**

These metallic glands are liquid tight, offer excellent strain relief and have lameller designed plastic inserts for protection against distortion. These glands are suitable for use in machinery and equipment, measuring and controlling devices, medical equipments and many other fields where exceptional stability and safe functioning is required. Cable glands with long thread length or reduced clamping range are also available on request.

**Technical Details**

Material  
Clamping Insert  
Protection Class  
Sealing Ring  
O Ring  
Temperature Range  
Threads available  
Approvals

Brass, Nickel Plated  
Polyamide 6  
IP 68  
Neoprene  
Perbunan (NBR)  
-40° C to + 100° C  
Pg, Metric and NPT  
VDE, HALOGEN FREE

**Pg Thread**

<b>Size</b>	<b>Cat. No.</b>	<b>Standard Pack (Pieces)</b>	<b>Thread Diameter (mm)</b>	<b>Thread Length (mm)</b>	<b>Spanner (mm)</b>	<b>Clamping Range (mm)</b>
-------------	-----------------	-------------------------------	-----------------------------	---------------------------	---------------------	----------------------------

<b>Pg 7</b>	BSBC-01	50	13	6	14	3 - 6.5
<b>Pg 9</b>	BSBC-02	50	16	6	17	4 - 8
<b>Pg 11</b>	BSBC-03	50	19	6	20	5 - 10
<b>Pg 13.5</b>	BSBC-04	50	21	6.5	22	6 - 12
<b>Pg 16</b>	BSBC-05	25	23	6.5	24	10 - 14
<b>Pg 21</b>	BSBC-06	25	29	7	30	13 - 18
<b>Pg 29</b>	BSBC-07	20	37	8	40	18 - 25
<b>Pg 36</b>	BSBC-08	15	47	10	50	22 - 32
<b>Pg 42</b>	BSBC-09	12	54	12	58	30 - 38
<b>Pg 48</b>	BSBC-10	12	59	14	64	34 - 44

#### NPT Thread

Size	Cat. No.	Standard Pack (Pieces)	Thread Diameter (mm)	Thread Length (mm)	Spanner (mm)	Clamping Range (mm)
NPT 3/8"	BNBC-01	50	16	15	17	4 - 8
NPT 1/2"	BNBC-02	50	21	13	22	6 - 12
NPT 3/4"	BNBC-03	20	29	13	30	13 - 18
NPT 1"	BNBC-04	20	33.2	13	43	18 - 25

#### Metric Thread

Size	Cat. No.	Standard Pack (Pieces)	Thread Diameter (mm)	Thread Length (mm)	Spanner (mm)	Clamping Range (mm)
M 12 x 1.5	BMBC-05	50	12	6	14	3 - 6.5
M 16 x 1.5	BMBC-01	50	16	7	17	4 - 8
M 16 x 1.5	BMBC-E1	50	16	7	20	5 - 10
M 20 x 1.5	BMBC-02	20	20	8	22	6 - 12
M 25 x 1.5	BMBC-03	20	25	8	24	10 - 14
M 25 x 1.5	BMBC-E3	20	25	8	27	11 - 17
M 32 x 1.5	BMBC-04	10	32	9	30	13 - 18
M 32 x 1.5	BMBC-E4	10	32	8	34	15 - 21
M 40 x 1.5	BMBC-05	10	40	9	40	18 - 25
M 40 x 1.5	BMBC-E5	10	40	9	43	19 - 28
M 50 x 1.5	BMBC-06	5	50	9	50	22 - 32
M 63 x 1.5	BMBC-07	5	63	14	64	34 - 44
M 72 x 1.5	BDSM-08	5	72	16	72	56 - 62
M 75 x 1.5	BDSM-09	5	75	18	77	56 - 65
M 80 x 1.5	BDSM-10	5	80	20	90	62 - 66
M 85 x 1.5	BDSM-11	5	85	22	92/95	67 - 77

#### ADDEESS:

**A1metallics INDIA** Plot- 1255, GIDC Industrial Estate, Shanker tekri Jamnagar 361004 Gujarat INDIA

#### CONTACTS:

PHONE : 91-22-43449300/99

FAX : 91-22-22834046

EMAIL : [sales@a1metallics.com](mailto:sales@a1metallics.com)

**[CONTACT US](#) | [BACK TO HOME PAGE](#)**

#### KEYWORDS:

**brass cable glands metric strain relief, strain relief, strain relief cord connectors, cable strain reliefs, brass cable glands, cable strain relief, pg cable glands, strain relief connector, strain relief for cables, cable gland with strain relief, cable glands, nickel plated brass cable gland, strain relief cable, connector strain relief, manufactures, exporters and suppliers from A1Metallics**