

Metric Cable Glands Brass Strain Relief

Brass Cable Glands Metric Strain Relief glands Nickel Plated Brass Cable glands



Metric Cable Glands Brass Strain Relief

New Page 1

Brass Cable Glands Metric Strain Relief glands Nickel Plated Brass Cable glands

These metallic glands are liquid tight, offer excellent strain relief and have lameller designed plastic inserts for protection against distortion. These glands are suitable for use in machinery and equipment, measuring and controlling devices, medical equipments and many other fields where exceptional stability and safe functioning is required. Cable glands with long thread length or reduced clamping range are also available on request.

Technical Details

Material
Clamping Insert
Protection Class
Sealing Ring
O Ring
Temperature Range
Threads available
Approvals

Brass, Nickel Plated
Polyamide 6
IP 68
Neoprene
Perbunan (NBR)
-40° C to + 100° C
Pg, Metric and NPT
VDE, HALLOGEN FREE

Pg Thread

| Size | Cat. No. | Standard Pack (Pieces) | Thread Diameter (mm) | Thread Length (mm) | Spanner (mm) | Clamping Range (mm) |
|------|----------|------------------------|----------------------|--------------------|--------------|---------------------|
|------|----------|------------------------|----------------------|--------------------|--------------|---------------------|

| | | | | | | |
|----------------|---------|----|----|-----|----|---------|
| Pg 7 | BSBC-01 | 50 | 13 | 6 | 14 | 3 - 6.5 |
| Pg 9 | BSBC-02 | 50 | 16 | 6 | 17 | 4 - 8 |
| Pg 11 | BSBC-03 | 50 | 19 | 6 | 20 | 5 - 10 |
| Pg 13.5 | BSBC-04 | 50 | 21 | 6.5 | 22 | 6 - 12 |
| Pg 16 | BSBC-05 | 25 | 23 | 6.5 | 24 | 10 - 14 |
| Pg 21 | BSBC-06 | 25 | 29 | 7 | 30 | 13 - 18 |
| Pg 29 | BSBC-07 | 20 | 37 | 8 | 40 | 18 - 25 |
| Pg 36 | BSBC-08 | 15 | 47 | 10 | 50 | 22 - 32 |
| Pg 42 | BSBC-09 | 12 | 54 | 12 | 58 | 30 - 38 |
| Pg 48 | BSBC-10 | 12 | 59 | 14 | 64 | 34 - 44 |

NPT Thread

| Size | Cat. No. | Standard Pack (Pieces) | Thread Diameter (mm) | Thread Length (mm) | Spanner (mm) | Clamping Range (mm) |
|----------|----------|------------------------|----------------------|--------------------|--------------|---------------------|
| NPT 3/8" | BNBC-01 | 50 | 16 | 15 | 17 | 4 - 8 |
| NPT 1/2" | BNBC-02 | 50 | 21 | 13 | 22 | 6 - 12 |
| NPT 3/4" | BNBC-03 | 20 | 29 | 13 | 30 | 13 - 18 |
| NPT 1" | BNBC-04 | 20 | 33.2 | 13 | 43 | 18 - 25 |

Metric Thread

| Size | Cat. No. | Standard Pack (Pieces) | Thread Diameter (mm) | Thread Length (mm) | Spanner (mm) | Clamping Range (mm) |
|------------|----------|------------------------|----------------------|--------------------|--------------|---------------------|
| M 12 x 1.5 | BMBC-05 | 50 | 12 | 6 | 14 | 3 - 6.5 |
| M 16 x 1.5 | BMBC-01 | 50 | 16 | 7 | 17 | 4 - 8 |
| M 16 x 1.5 | BMBC-E1 | 50 | 16 | 7 | 20 | 5 - 10 |
| M 20 x 1.5 | BMBC-02 | 20 | 20 | 8 | 22 | 6 - 12 |
| M 25 x 1.5 | BMBC-03 | 20 | 25 | 8 | 24 | 10 - 14 |
| M 25 x 1.5 | BMBC-E3 | 20 | 25 | 8 | 27 | 11 - 17 |
| M 32 x 1.5 | BMBC-04 | 10 | 32 | 9 | 30 | 13 - 18 |
| M 32 x 1.5 | BMBC-E4 | 10 | 32 | 8 | 34 | 15 - 21 |
| M 40 x 1.5 | BMBC-05 | 10 | 40 | 9 | 40 | 18 - 25 |
| M 40 x 1.5 | BMBC-E5 | 10 | 40 | 9 | 43 | 19 - 28 |
| M 50 x 1.5 | BMBC-06 | 5 | 50 | 9 | 50 | 22 - 32 |
| M 63 x 1.5 | BMBC-07 | 5 | 63 | 14 | 64 | 34 - 44 |
| M 72 x 1.5 | BDSM-08 | 5 | 72 | 16 | 72 | 56 - 62 |
| M 75 x 1.5 | BDSM-09 | 5 | 75 | 18 | 77 | 56 - 65 |
| M 80 x 1.5 | BDSM-10 | 5 | 80 | 20 | 90 | 62 - 66 |
| M 85 x 1.5 | BDSM-11 | 5 | 85 | 22 | 92/95 | 67 - 77 |

ADDEESS:

A1metallics INDIA Plot- 1255, GIDC Industrial Estate, Shanker tekri Jamnagar 361004 Gujarat INDIA

CONTACTS:

PHONE : 91-22-43449300/99

FAX : 91-22-22834046

EMAIL : sales@a1metallics.com

[CONTACT US](#) | [BACK TO HOME PAGE](#)

KEYWORDS: